



## TrinaCommercial 18 Power

Trina Energy Storage Solutions for Commercial Application



**Most Affordable High-Quality Commercial Solution**

**Rated Power: 18 kW (Three-phase)**

**Capacity: 30 kWh**

**Warranty: 10 years Battery Performance (Expected Lifetime 20 years)**



Proven Safety



Reliable Performance



Visualisation



Plug & Play



Multi-Function



Easy Installation



Self-Consumption

Germany:  
Trina Energie Storage Vertrieb und Service GmbH  
Tel: +49 (0) 69 75844 361  
Email: eu.sales@trinabess.com  
Add: Otto-Schoff-Str. 4, 60438, Frankfurt, Germany

Oceania:  
Trina Energy Storage Solutions (Australia) Pty. Ltd.  
Tel: +61 2 8034 6313  
Email: australia.sales@trinabess.com  
Add: Suite 60, 20 - 28 Maddox Street, Alexandria, NSW 2015, Australia

China:  
Trina Energy Storage Solutions (Jiangsu) Co., Ltd.  
Tel: +86 519 8517 6686  
Email: trinabess@trinasolar.com  
Add: No. 2 Tianhe Road, Trina PV Park, New District, Changzhou, Jiangsu

America:  
Sales and Technical Representation  
Tel: +1 800 696 7114  
Email: us.sales@trinabess.com  
Add: 100 Century Center, Suite 501, San Jose CA 95112

Japan:  
Trina Energy Storage Japan Co., Ltd.  
Tel: +81 (0) 3 6432 0581  
Email: jp.sales@trinabess.com  
Add: 21F World Trade Center Building, 4-1, 2-chome, Hamamatsu-cho, Minato-ku, Tokyo 105-6121 Japan

## Specifications

### Inverter Parameters (PCS)

#### Battery Input (DC)

Max. Input Power	18 kW
Operation Voltage Range	250 - 800 V
Max. Charging Current	40 A
Max. Discharging Current	40 A

#### AC Output

Max. Output Power	18 kW
Rated Output Voltage	3N - 400 Vac
Rated Output Frequency	50 Hz
AC Nominal Current	26.1 A
Back-up Function (Optional)	Auto-switching to backup power after approx. 5 sec

#### Other

IP Protection Class	IP 65
Noise	< 55 dB
Dimension (W x H x D)	540 x 670 x 275 mm
Weight	60 kg
Cooling	Forced Air Cooling
Certificate	VDE 4105, IEC 62109, IEC 62477

#### Battery Parameters

Battery Capacity	30 kWh
Nominal Voltage	672 V
DOD	90 %
Cycle Life	Approx. 8000
Module Weight	350 kg
Communication	CAN 2.0, RS 485
Certificate	TUV, CE, UL, UN 38.3
IP Protection Class	IP 20

#### System

Dimension (W x H x D)	1300 x 1950 x 750 mm
Operating Temperature Range	-10 ~45 °C (-10 ~0 °C only discharge)
Weight	735 kg
Warranty	10 years battery performance (Expected lifetime 20 years)

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

